



# U-PILLAR Underground service connection boxes

For up to 6x 63 A, 4x 100A or 1x3-phase 160 A services



**The U-Pillar is a new concept in service connections for branching networks. Building on Hiko's expertise in underground switchgear, the U-Pillar delivers a simple, robust, secure, cost effective and fully underground solution for 63 A / 100 A service fuses and 160 A DIN standard disconnects.**

In the U-Pillar, fusegear is locked and protected, below ground level, where it is kept clean and dry, even in flood conditions.

The unique design also provides for safe and convenient inspection and maintenance above ground level, without the need to pump out water.

Another key feature of the U-Pillar is the free movement of air around the fusegear, which eliminates concerns around operational safety and long-term reliability associated with other underground solutions that rely on so-called "waterproof" fuse housings. These typically include seals that may be vulnerable to the pressure

cycling that occurs as the temperature of the service fuse varies between hot and cold. When air is drawn in, moisture condenses inside the housing, and is not expelled when the fuse heats up again. Water in contact with a fuse causes operational hazards, reduced asset lifetime, and elevates the risk of in-service failure.

The U-Pillar comes complete with water-blocked, pre-terminated flexible tails for both the incomer and service supplies. So network operators can be certain that the integrity of the asset is not compromised by water ingress via a damaged or poorly maintained service cable. And service connection contractors do not need to open the box.

The reinforced lid of the U-Pillar is extremely robust, for installation in footpaths and driveways, and is available in a range of colours.

The pit is shaped to provide structural strength and long-term stability. Materials used are benign to the environment, and resistant to engine oil, petrol and diesel.

## U-PILLAR Underground service connection boxes

### Mechanical specifications

Parameter	Test method	Requirement	Comments
Lid load class	AS3996	Class B080 (8 tonnes)	Suitable for footpaths and driveways (nominal wheel loading 2,670 kg)
Lid slip resistance	AS/NZS4586	Classification V (P5)	Represents a very low risk of slipping when wet
Colour	-	Black	Other colours available on request
Weather resistance	ASTM D2565 / ISO 4892-2	Greater than UV8	Long term UV stable
Chemical resistance	-	Engine oil, petrol, diesel	Maintains structural integrity after exposure to small and occasional spills
Flammability	UL94	HB	Very difficult to ignite without a sustained source of ignition
Thermal stability	AS/NZS4766	Pass	Melt flow index remains within $\pm 20\%$ after 100 days at 100°C
Temperature range	-	-40 to +60°C	Hot tarseal can be used around pit headframe

### Materials

Parameter	Test method	Comments
Lid, pit	Polyolefin	UV stabilised grade suitable for external water tanks
Bell	Composite	-
Stand	Polycarbonate	-
Fusegear holders	ABS, various	-
Fixtures and fittings	Stainless steel	304, (1.4301)
Cable insulation	Thermoset elastomeric PVC	Submersible, splash resistant to petrol and oil, ozone resistant, abrasion resistant

### Configurations and dimensions

Hiko Code	Number of services						Dimensions		Approx weight (kg)	Cable tail sections		In-line connectors	
	63 A		100 A		160 A		Width (mm)	Depth (mm)		Incomers (mm²)	Services (mm²)	Incomers (mm²)	Services (mm²)
	1-phase	3-phase	1-phase	3-phase	1-phase	3-phase							
UDP02B0630011	6								19.0				
UDP02B0630012		2							17.6				
UDP02B1000013			1						14.4				
UDP02B1000014			2						15.3	25	16	10-50	10-50
UDP02B1000015			3						16.2				
UDP02B1000016			4						17.1				
UDP02B1000017				1					16.4				
UDP02B1600020					3				25.0				
UDP02B1600021						1			21.8	70	70	35-120	35-120

#### Options

Security bolts / internal padlock  
Identification (on lid and bell)

Incomer and service cable tail lengths (0.2 m and 0.3 m as standard)<sup>1</sup>  
Branch joint<sup>2</sup>  
Service fuses  
Street lighting and other auxiliary supplies

#### Notes

1. Capped incomer and water-blocked service connectors included as standard
2. Hiko product code KP8033 (Pfisterer ISICOMPACT single-shear-bolt connector and resin joint kit) for main 50-240 / branch 10-70 mm².

#### Other literature available on request

Test reports, drawings, technical data sheets, installation instructions, O&M guidelines, FMEA